

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
22 April 2004 (22.04.2004)

PCT

(10) International Publication Number
WO 2004/033982 A1

- (51) International Patent Classification⁷: **F41A 3/12**
- (21) International Application Number:
PCT/US2003/030471
- (22) International Filing Date:
26 September 2003 (26.09.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/417,522 9 October 2002 (09.10.2002) US
- (71) Applicant and
(72) Inventor: **MOORE, Wildey, J.** [US/US]; 45 Angevine Road, Warren, CT 06794 (US).
- (74) Agent: **CRUTCHER, William, C.**; McCormick Paulding & Huber, LLP, CityPlace II, 185 Asylum Street, Hartford, CT 06103 (US).
- (81) Designated States (*national*): AE, AU, BA, BR, BZ, CA, CN, CO, CR, DZ, EC, GE, HR, IL, IN, JP, KE, KR, LT, LV, MA, MG, MK, MX, NO, NZ, OM, PH, PL, SD, SG, SY, TN, UA, US, UZ, VN, YU, ZA.
- (84) Designated States (*regional*): Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).
- Published:**
— with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: FIREARM WITH A READILY INTERCHANGEABLE BOLT FACE



(57) Abstract: A readily replaceable bolt face for a firearm (10) with a movable slide (12) that strips a round from a magazine, extracts the spent round from the firing chamber and then ejects the round from the firearm by means of an ejector. A bolt face insert (32) has an external configuration that is common to a range of calibers, but with a bolt face side (66) designed to fit the rim of a specific caliber or calibers having the same rim dimension. The insert may be replaced to fit a different caliber without replacing the slide. The bolt face insert is provided with a slot (62) for the ejector and a groove (60) to accept an extractor for the specified caliber.